

- >> Accurate High Temperature ceramic Pt 100 RTD
- >> The single point sensor is encapsulated in a 6.35 mm OD 304 stainless steel probe
- >> Easily fitted to a FX-TW thermowell with 1/2" threads
- >> Optional probe lengths



High temperature measurement






The probe temperature sensor FX-TES-PT100-HT utilizes a precision, high temperature rated platinum RTD sensor that is encapsulated in 6.35 mm (0.25") OD, 304 series stainless steel probe and is available in various lengths . It can be installed in the side of an exhaust stack to monitor the flue gas temperatures or with FX-TW thermowell to pipes carrying liquid or steam at high temperatures. The rigid stainless steel probe and the Weather proof Metal casing make the sensor suitable for most HVAC applications. The standard length of the probe is 200mm. The immersion type probes are installed in the appropriate length thermowell for the pipe size. Thermal conductive compound should be added inside the thermowell to provide optimum thermal transfer.

The FX-TW series thermowells are machined lathed from 1" barstock stainless steel. Thermowells have 1/2" NPT external thread and 1/2" NPSM internal thread.

Technical features

Sensor Type:	High Temperature rated Pt100 RTD
Sensor Accuracy:	±0.3°C
Probe Temperature Range:	-100 to 600°C
Probe Lengths:	100 mm, 50 mm, 150 mm, 200 mm, 300 mm, 450 mm
Probe Material:	304 Series Stainless Steel
IP protection class:	IP64
Probe Dimensions:	6.35 mm (0.25") Diameter
Termination:	Screw Terminal block
Manufacturing Process:	ISO9001
Ambient Temperature:	0 - 70°C
Ambient Humidity:	0-95% RH

Dimensions



150 mm and up machined thermowells have a two step stem as shown. Welded construction have a 0.375" (9.5 mm) diameter.

Part numbers

FX-TES-PT100-HT200
FX-TW200

High Temperature Pt100 RTD, 200 mm probe, default length
Thermowell 200mm (required only for immersion type)

FX-TES-PT100-HT50
FX-TES-PT100-HT100
FX-TES-PT100-HT150
FX-TES-PT100-HT300
FX-TES-PT100-HT450

50 mm probe
100 mm probe
150 mm probe
300 mm probe
450 mm probe

FX-TW50 Thermowell 50mm
FX-TW100 Thermowell 100mm
FX-TW150 Thermowell 150mm
FX-TW300 Thermowell 300mm
FX-TW450 Thermowell 450mm